

Index

Index

- anti friction slides, 14, 61
- backlash, 14, 60, 61
- barrel shape
 - cam deformation, 55
 - guide setting, 8
 - regulating wheel truing, 9
 - truing, 54
 - truing and regulating
 - wheel angle, 7, 53
 - workrest blade, 8, 54
- bend of workpiece
 - grinding cut pressure, 4, 49
 - Hardening Stress, 4, 49
 - heat generation, 4, 49
 - measurement, 1, 48
 - stock removal, 48
 - Stock removal, 1
 - stock removal
 - calculation, 3
 - surface finish
 - irregularities, 2, 49
- blotters
 - re-tightening, 21
- burn
 - diamond, 36
 - workpiece, 37, 39, 76, 79
- cam deformation, 55, 57, 70
- chatter, 19, 32, 42, 65, 81
 - regenerative, 74
- compensation
 - size, 14, 18, 60, 61, 64
- contact line, 7, 10, 25, 46, 53
- coolant
 - contaminated, 27
 - diamond tooling, 36
 - flow rate, 4, 20, 40, 49, 66, 78
 - lubricity, 4, 34, 49
 - nozzle, 41, 79
 - temperature, 17, 63
- Cpk, 14, 62
- cylindricity, 1, 48
 - workrest blade, 8, 54
- damage
 - workpiece, 37, 76
 - workrest blade, 47, 70, 85

Index

- diamond roll, 24, 26, 39, 74, 78, 85
- diamond tool, 9, 10, 13, 23, 28, 31, 36, 39, 50, 59, 71, 72, 77, 85
 - regulating wheel, 69
- dressing, 22, 24, 46, 50, 69, 70, 73
- dressing traverse rate, 25, 27, 35, 36, 39, 78
- feed angle, 8, 25, 38, 46, 88
- fire line, 10, 16, 17, 25, 39
- gibb, 52, 54, 61, 72
- grinding gap, 30
- grinding swarf, 15, 27, 29
- grinding wheel
 - growth, 17, 63
 - hard acting, 38, 77
 - out of roundness, 23, 72
 - spindle, 42, 81
 - spindle bearing, 24, 28, 73, 74
 - unbalance, 42, 81
- grinding wheel speed, 29, 38, 77
- grinding wheel wear, 5, 13, 16, 18, 26, 29, 30, 50, 63
- guide setting, 5, 8, 10, 31, 32
- height above center, 19, 44, 45, 65, 74, 82, 83, 88
- lobes, 19, 65
- low center
 - contact line, 10
 - guide setting, 10
 - regulating wheel housing, 9
 - truing angle, 9
 - wheel housing, 57
- low end on workpiece, 10
 - guide setting, 11
 - interrupted flow, 11
 - regulating wheel spindle bearings, 11
- lubrication
 - slide, 15, 61
 - spindle, 51
 - truing, 69
- machine stiffness, 44, 46, 74, 80, 82, 84

Index

- machine warm up, 17, 63
- material sticking, 33
- out of roundness, 16, 19, 65
- chatter, 46
- flats, keyways, slots, holes, 20, 65
- grinding wheel spindle, 23, 74
- large surface finish variance, 28
- light weight material, 20, 66
- out of balance, 21, 67
- regulating wheel, 21, 67, 68
- size variance, 12, 58
- trailing edge of work piece, 20
- part to part size variance
 - dark and light spots, 12, 58
 - diamond, 13, 59
 - regulating wheel bearings, 13
 - regulating wheel quality, 12, 58
 - pinch out test, 13, 59
 - recrystallization, 38, 77
 - regulating wheel
 - dark rings, 12, 21, 58, 67
 - dark spots, 12, 21, 58, 67
 - holes, 21, 67
 - metal chips, 21, 67
 - quality, 12, 21, 58, 67, 70
 - regulating wheel bearing, 7, 11, 13, 22, 52, 59, 71, 74
 - regulating wheel wear, 51, 69, 70
 - rocking lower slide, 52
 - scratches, 27
 - size tolerance, 9, 12, 14, 17, 57, 58, 61, 63, 79
 - spark out test, 22, 59, 71
 - spindle bearing
 - diamond roll, 24, 74
 - grinding wheel, 24, 28, 73, 74
 - regulating wheel, 7, 11, 22, 52, 71

Index

- spindle drive belt, 43, 74, 82**
- spindle orbits, 22, 71**
- stick slip**
 - slide, 14, 61**
 - truing, 69**
- Straightness, 1, 48**
 - error correction, 2, 49**
 - workrest blade, 8, 70**
- sudden size change, 16, 60, 61**
- super finishing, 38, 77**
- surface finish, 2, 5, 16, 24, 26, 34, 35, 39, 49, 74, 78, 80, 85, 95**
 - diamond roll, 26**
 - fire line, 25**
 - grit size, 26**
 - sudden changes, 29**
 - throughfeed rate, 26**
 - too high, 25**
 - traverse rate dressing, 25**
- swivel plate, 5, 10, 15, 25, 31, 39, 50, 51, 62**
- taper**
 - guide setting, 5**
 - Loose regulating wheel spindle bearings, 7**
 - realign guide, 7**
 - swivel plate, 5**
 - wheel wear, 5**
- truing**
 - accuracy, 54**
 - angle, 7, 9, 25, 46, 53, 110**
 - device, 17**
 - device flexing, 22**
 - errors, 10**
 - stick slip, 69**
 - tool wear, 35**
 - tools, 71**
 - traverse rate, 35, 39, 78**
 - wear, 23, 36, 54, 57**
- vibration, 42, 74, 81**
- wheel breakdown, 62**
- work guide adjustments, 87**
- workrest blade, 8, 32, 33, 47, 54, 68, 70, 84**
 - damage, 47**